



POWER FAILURE ALARM

The **Receptacle Mount Power Failure Alarm** guarantees that your 120 VAC Device is Plugged-In and Getting Power!!! Always On Duty, It Insures Reliable Power for Freezers, Heating Systems, Control Systems, Medical Equipment and more.

IF a Device is Unplugged or Power Fails:

- 103db Alarms Sounds
- Red **LED** Flashes
- Flashlight Illuminates Area (Optional)
- NO or NC Relay Energizes; Alarm System, Phone Dialer or other Devices (Optional)

Some Features:

- Silence or Test Pushbutton
- Convenient 120 VAC @ 15 AMP Pass-Through Receptacle
- Selectable Snooze Alarm Time Ranges
- 10 Year Lithium Battery Included Low Battery Alarm



POWER FAIL ALARM MODEL PFA-1

SPECIFICATIONS

- Power consumption (idle) 11 micro-amps
- Power consumption (alarm)..... 30 mA
- Maximum current..... 15A
- Piezo buzzer volume 103 dB at 2 feet
- Piezo buzzer diaphragm stainless steel
- Maximum load 15A
- Operating temperature..... -40C to 65C
- Box size (mm)..... 105 tall x 67deep x 55W
- Box material polystyrene
- Weight without battery 181g
- Output current 9V
- Output contact closure..... 24V - 50mA maximum



POWER FAIL ALARM MODEL PFA-4

Outlet Mount Models

PFA-1 - Standard model. Electrical socket mount.

PFA-2 - Like PFA-1 but includes an output (N.O. or N.C.) for connection to external devices like building alarms. Connected by cable to your external device. Cable optional.

PFA-4 - Electrical socket mount like PFA-1 but includes a built-in flashlight.

Order from: **C A Briggs Company**

622 Mary Street; Suite 101; Warminster, PA 18974

Phone: 267-673-8117 - Fax: 267-673-8118

Sales@cabriggs.com - www.cabriggs.com

POWER FAILURE ALARM

The **Wall Mount Power Failure Alarm** guarantees that your 85 to 265 VAC Device is Connected and Getting Power!!! Always On Duty, It Insures Reliable Power for Freezers, Heating Systems, Control Systems, Medical Equipment and more.

IF a Device is Unplugged or Power Fails:

- 103db Alarms Sounds
- Red **LED** Flashes
- Flashlight Illuminates Area (Optional)
- NO or NC Relay Energizes; Alarm System, Phone Dialer or other Devices (Optional)

Some Features:


- Rugged Weatherproof Enclosure
- Silence or Test Pushbutton
- Power 85 to 265 VAC @ 15 AMP
- Selectable Snooze Alarm Time Ranges
- 10 Year Lithium Battery Included Low Battery Alarm




POWER FAIL ALARM MODEL PFA-5

SPECIFICATIONS

- Power consumption (idle) 11 micro-amps
- Power consumption (alarm)..... 55 mA
- Voltage range..... 85-250VAC, 50-60Hz
- Piezo buzzer volume 103 dB at 2 feet
- Piezo buzzer diaphragm stainless steel
- Operating temperature..... -40C to 65C
- Box size..... 4 x 4 x 2 inch (100x100x50mm)
- Box material PVC
- Output current 9VDC
- Output contact closure.....24V - 50mA maximum



120 VAC Plug



200/250 VAC Plug

Wall Mount Models

PFA-5 (120VAC) - with a NEMA 5-15 plug and 10 foot rubber [SJOOW](#) cord.

PFA-6 (250VAC) - for voltages from 200-250VAC. Comes with 10 foot (3m) rubber jacketed [SJOOW](#) cord and choice of plug. (Euro, UK, Australia/NZ, NEMA 6-15)

Order from: **C A Briggs Company**

622 Mary Street; Suite 101; Warminster, PA 18974

Phone: 267-673-8117 - Fax: 267-673-8118

Sales@cabriggs.com - www.cabriggs.com