

The Levelpro ITC 650 Universal Data Logger can display current and record values from 8 different measuring channels. Each channel can be individually designated (described) with any engineering measuring unit. The LCD graphical display allows for visualization of the values from all 8 channels simultaneously. A significant advantage is possibility of viewing the trends in each measuring channel.

- Temp
- Flow
- Pressure
- PH
- Level
- Humidity
- Current



FEATURES

- Universal Multi-Channel Indicator
- LCD Graphic Display
- Up to 8 inputs Universal | 4-20mA
- 2 Electronic Relay Outputs
- 24VDC Power Supply Output:
24VDC | 200mA
Will Power All 8 Channels
- RS-485 | Modbus RTU Standard
- Temperature | Flow | Humidity | Pressure |
PH | Redox | Level | Current
- Viewing the Trends in each of the
8 Measuring Channels
- Any Text Description Possible: Name and Units
- Data transfer to the Master System via RS-485
- Password Protected

ORDERING

ITC 650-99-X128-1-X

number of channels:

- 2 : 2 x 4-20mA
- 4 : 4 x 4-20mA
- 8 : 8 x 4-20mA

power supply:

- 3 : 24VAC | DC
- 4 : 85V - 260VAC | DC



SPECIFICATIONS

Power Supply	120VAC - 24VDC
Power Consumption	typical 7VA max. 12VA
Display	Back-lit Graphic LCD 128 x 64 points
Measuring Inputs	2 4 8 inputs 0/4-20mA
Displayed Values Range	± 9999 + decimal point
Accuracy	0.1% @ 25°C
Stability	50 ppm °C
Digital Outputs	non-volatile memory EPROM type
Relays Outputs	2 electronic relays NO type (ER1, ER2 with max. load 24VAC 35VDC 200mA
Transducer Power Supply Output	24VDC ±5% max. 200mA, stabilized, not insulated from measuring inputs
Communication Interface	RS-485, 8N1 and 8N2, 1200 bit/s ÷ 115200 bit/s, Modbus RTU galvanically separated
Operating Temperature	-10°C - +70°C
Protection Class:	IP 65 (front), available options: additional frame IP 65 for panel cutout sealing, transparent door STD-99, see: accessories; IP 20
Case	NEMA 4X Face Plate
Case Material	NORYL - GFN2S E1
Case Dimensions	96 x 96 x 100 mm
Panel Cut-Out Dimensions	90.5 x 90.5 mm
Installation Depth	min. 102 mm
Board Thickness	max. 5 mm