

OEM Flowmeter with Switch



measuring
•
monitoring
•
analyzing

BVO



- Flow Ranges 0.1...1.0 GPM to 1.0...13 GPM
- Repeatability: $\pm 2\%$ of Full Scale
- Brass or Stainless Steel Wetted Parts
- Adjustable Switch Standard



KOBOLD companies worldwide:

Order from: **C A Briggs Company**

622 Mary Street; Suite 101; Warminster, PA 18974

Phone: 267-673-8117 - Fax: 267-673-8118

Sales@cabriggs.com - www.cabriggs.com

KOBOLD Instruments, Inc.
1801 Parkway View Drive
Pittsburgh, PA 15205



OEM Flowmeter with Switch Model BVO

Description

Cost conscious, large volume applications require special products. The KOBOLD BVO line of flowmeters is designed for customers requiring a low cost flowmeter that is both rugged and reliable. Due to a streamlined production process, the BVO series offers exceptional value for many flow monitoring applications involving water-like liquids. The BVO offers both the design considerations and high quality of the KOBOLD SV line of flow meters, only at a lower price. The repeatability of the device is $\pm 2\%$. The switch supplied with each BVO is adjustable over the meter's entire operating range.



Specifications

Accuracy:	$\pm 10\%$ Full Scale
Repeatability:	$\pm 2\%$ Full Scale
Media:	Water-like Liquids
Mounting:	Vertical, Upward Media Flow
Measuring Principle:	Float with Cylindrical Control Tube
Temperature Range:	$-10 \dots 212$ °F
Maximum Pressure:	145 PSIG
Housing:	Gold Anodized Aluminum
Fittings:	NPT Standard

Wetted Parts

Brass Meters: Ni-Plated Brass, NBR, Glass

SS Meters: 304 SS, FKM, Glass

Fittings: NPT Standard

Switch Housing: Plastic

Measuring Tube: Borosilicate Glass

Electrical Protection: IP65

Reed Contact: Standard: N/O, Optional: SPDT
 Max. 230 VDC/0.26 A/60 W
 60 VDC/1 A/60 W
 Max. 240 VAC/0.42 A/100 W
 100 VAC/1 A/100 W
 cCSAus Approved

Order Details (Example: BVO-6216U)

Range (GPM Water)	Fittings (NPT)	Pressure Loss at Max Flow (PSIG_)	Model Number	
			Brass	304 SS
0.1...1.0	¼"	0.9	BVO-6102	BVO-6202
0.2...2.0	¼"	1.4	BVO-6106	BVO-6206
1.0...5.0	½"	1.1	BVO-6116	BVO-6216
1.0...13	1"	2.1	BVO-6150	BVO-6250
Options (Add Suffix to Order Number)				
Suffix ..U = SPDT Switch in Place of N/O Switch				