Pendulum Level Monitor

for Bulk Solids



measuring • monitoring

analyzing





Order from: C A Briggs Company

KOBOLD Instruments, Inc. 1801 Parkway View Drive Pittsburgh, PA 15205

622 Mary Street; Suite 101; Warminster, PA 18974 Phone: 267-673-8117 - Fax: 267-673-8118 Sales@cabriggs.com - www.cabriggs.com



mm,

Description

The KOBOLD PLS monitors the maximum fill level of bulk solids in storage tanks and silos. The monitor consists of two parts: the aluminum connection housing with the microswitch and the connection terminals and the pendulum rod with the measuring cone. The PLS is installed vertically on the side of the filling piece. When a silo is filled with bulk solids, the rising level causes the measuring cone of the level monitor to swing to the side. This movement is directly transferred from the pendulum rod to the microswitch.

Applications

- For Most Bulk Solids
- Cereal
- Flour
- Granulated Plastic
- Cement
- Sand
- Sugar

Technical Details


Measuring Principle: Installation Length:	Pendulum 500 mm, 1000 mm, 1200 m 1500 mm, 2000 mm	
	(Others on Request)	
Media Temperature:	Max. 176 °F	
Ambient Temperature:	-13176°F	
Operating Pressure:	-3" Hg 7 PSIG	
Mounting Position:	Vertical	
Min. Bulk/Solid Density:	0.3 kg/dm ³	
Connection Housing:	Aluminum	
Process Flange:	Aluminum	
Bellows:	NBR	
Pendulum Rod:	Aluminum, 8 mm	
Cone:	Aluminum	
Electrical Connection:	Via Cable Gland M 20 x 1.5	
Contact:	Microswitch (SPDT Switch)	
Electr. Switching Values:	Max. 250 V _{AC} /15 A	
Protection:	IP 66	

Order Details (Example: PLS-200 00 05)

Model	Approval	Pendulum Length "L"
PLS-200	00 = Without	05 = 500 mm 10 = 1000 mm 12 = 1200 mm 15 = 1500 mm 20 = 2000 mm YY = Special Length

Mounting Example

Electrical Connection



Dimensions

